

**MATERIAL SAFETY DATA SHEET**
**NEOT Diesel -10/-20, NEOT Diesel -10/-20 Premium, NEOT Diesel -25/-35, NEOT Diesel -25/-35 Premium, NEOT Diesel -30/-38, NEOT Diesel -30/-38 Premium**
**Date:** 01.01.2019

**Former date:** 19.03.2018

**SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING**
**1.1 Product identifier**

<b>Trade name</b>	NEOT Diesel -10/-20, NEOT Diesel -10/-20 Premium, NEOT Diesel -25/-35, NEOT Diesel -25/-35 Premium, NEOT Diesel -30/-38, NEOT Diesel -30/-38 Premium
<b>Company product code</b>	NEDI -10, NEDI -10 Premium, NEDI -25 NEDI -25 Premium, NEDI -30, NEDI -30 Premium
<b>REACH registration number</b>	See section 3.2.

**1.2 Relevant identified uses of the substance or mixture and uses advised against**

<b>The uses of the chemical</b>	Distribution of Substance Use as a fuel Use of substance in Explosives Manufacture and Use Use in Road and Construction Applications See section 16 for PROC/SU/ERC-codes for identified uses.
---------------------------------	--

**1.3 Details of the supplier of the safety data sheet**

<b>Manufacturer, importer, other undertaking</b>	
	North European Oil Trade Oy
<b>Street address</b>	Urho Kekkosen katu 5C
<b>Postcode and post office</b>	FI-00100 Helsinki
<b>Post-office box</b>	P.O. Box 55
<b>Postcode and post office</b>	00088 S-RYHMÄ
<b>Telephone number</b>	+358 10 402 7001
<b>E-mail address</b>	tuotelaatu@neot.fi
<b>Finnish Business ID (Y code)</b>	1801056-5

**1.4 Emergency telephone number**

General emergency telephone number 112

Poison Information centre (in Finland), open 24 h daily  
PL 340 (Haartmaninkatu 4)  
00029 HUS  
(09) 471977 or (09) 4711

**SECTION 2: HAZARDS IDENTIFICATION**
**2.1 Classification of the substance or mixture**
**1272/2008 (CLP)**

Flam. Liq. 3, H226  
Acute Tox. 4, H332  
Skin Irrit. 2, H315  
Carc. 2, H351

**MATERIAL SAFETY DATA SHEET**

**NEOT Diesel -10/-20, NEOT Diesel -10/-20 Premium, NEOT Diesel -25/-35, NEOT Diesel -25/-35 Premium, NEOT Diesel -30/-38, NEOT Diesel -30/-38 Premium**

**Date:** 01.01.2019

**Former date:** 19.03.2018

STOT RE 2, H373  
Asp. Tox. 1, H304  
Aquatic Chronic 2, H411

**67/548/ETY – 1999/45/EY (DSD/DPD)**

Xn, N: R20-38-40-65-66-51/53, carc. cat. 3

---

**2.2 Label elements**

---

**1272/2008 (CLP)**

GHS02-GHS07-GHS08-GHS09



Signal word: **DANGER**

Contains: Fuels, diesel and distillates, C8-26 branched and linear; Renewable hydrocarbons (diesel type fraction)

**Hazard statements**

H226 Flammable liquid and vapour.  
H304 May be fatal if swallowed and enters airways.  
H315 Causes skin irritation.  
H332 Harmful if inhaled.  
H351 Suspected of causing cancer.  
H373 May cause damage to organs through prolonged or repeated exposure.  
H411 Toxic to aquatic life with long lasting effects.

**Precautionary statements**

P210 Keep away from heat / sparks / open flames / hot surfaces. — No smoking  
P261 Avoid breathing fume.  
P301+310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.  
P331 Do NOT induce vomiting.  
P302 + P352 IF ON SKIN: Wash with plenty of soap and water.  
P273 Avoid release to the environment.

---

**2.3 Other hazards**

---

Evaporates slowly. Oil mist may irritate eyes and the respiratory tract.

Risk of soil and groundwater contamination.

**MATERIAL SAFETY DATA SHEET**
**NEOT Diesel -10/-20, NEOT Diesel -10/-20 Premium, NEOT Diesel -25/-35, NEOT Diesel -25/-35 Premium, NEOT Diesel -30/-38, NEOT Diesel -30/-38 Premium**
**Date:** 01.01.2019

**Former date:** 19.03.2018

**SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS**
**3.2 Hazardous ingredients**

Name of the ingredient	CAS-number	EC-number	REACH-registration number	Concentration	Classification
Fuels, diesel	68334-30-5	269-822-7	01-2119484664-27-XXXX	0-100 %	CLP: Flam. Liq. 3, H226; Asp. Tox. 1, H304; Skin irrit. 2, H315; Acute Tox 4, H332; Carc. 2, H351; STOT RE2, H373; Aquatic Chronic 2, H411  DSD/DPD: Xn, N: R20, R38, Carc. Cat 3, R40, R51/53, R65
Renewable hydrocarbons, diesel type fraction	-	700-916-7 / 618-882-6 / 700-571-2	01-2120052680-62-XXXX / 01-2119450077-42-XXXX / 01-2120043692-58-XXXX	0-100 %	CLP: Asp. Tox. 1, H304; Skin irrit. 2, H315; STOT RE2, H373; Aquatic Chronic 3, H412  DSD-DPD: Xn; R65, Xn; R48/21/22, Xi; R38 R52-53
Distillates (Fischer-Tropsch), C8-26 branched and linear	848301-67-7	-	01-0000020119-75	0-100 %	CLP: Asp. Tox. 1, H304; EUH066  DSD/DPD: Xi; R65, R66
Fatty Acid Methyl Esters (FAME)	67762-38-3	267-015-4	01-2119471664-32-XXXX	0-7 %	Not classified.

**3.3 Other information**

Mixture of renewable raw material diesel, petroleum product, Fatty Acid Methyl Esters (FAME) and additives.

Renewable hydrocarbons (diesel type fraction, EC-no: 618-882-6): Identity outside the EU (CAS-number and name of the ingredient): Alkanes, C10-20, branched and linear, CAS 928771-01-1.  
Renewable hydrocarbons (diesel type fraction, EC-no: 700-916-7): Predominantly rich in saturated hydrocarbons with a carbon number range from C9 to C20. The substance contains benzene  $\geq 0$  to < 0.1 % (w/w), naphthalene  $\geq 0.001$  —  $\leq 0.5$  % (w/w) and n-hexane  $\geq 0$  to < 2.0 % (w/w).

**SECTION 4: FIRST AID MEASURES**
**4.1 Description of first aid measures**
**Inhalation:**

If oil mist has been inhaled, remove victim to fresh air and obtain medical attention (risk of chemical pneumonitis).

**Skin contact:**

**MATERIAL SAFETY DATA SHEET**

**NEOT Diesel -10/-20, NEOT Diesel -10/-20 Premium, NEOT Diesel -25/-35, NEOT Diesel -25/-35 Premium, NEOT Diesel -30/-38, NEOT Diesel -30/-38 Premium**

**Date:** 01.01.2019

**Former date:** 19.03.2018

Remove contaminated clothing, preferably after several minutes in safety shower (evaporation of liquid may cause fire hazard). Wash the skin with plenty of water and soap. If skin irritation persists, consult a physician.

**Eye contact:**

Rinse immediately with plenty of water, also under the eyelids. Continue irrigation for at least 15 minutes while moving eyes to extreme positions. If irritation, blurred vision or other symptoms persist, consult a physician (risk of corneal injury).

**Ingestion:**

DO NOT INDUCE VOMITING. If vomiting occurs, help to keep the victim's head down so that aspiration into the lungs will not occur. Obtain medical assistance immediately (risk of aspiration into the lungs and fatal chemical pneumonia especially if nausea or irritation occurs).

**4.2 Most important symptoms and effects, both acute and delayed**

Harmful if inhaled. Oil mist may irritate respiratory organs and cause fatal chemical pneumonia. The following signs and symptoms may appear and be either acute or delayed: fever, shortness of breath, chest pain, difficulty in breathing, coughing etc. Oil mist may irritate eyes. Respiratory symptoms may occur immediately or several hours after exposure.

**4.3 Indication of any immediate medical attention and special treatment needed**

Treat symptomatically. May cause fatal chemical pneumonia.

**SECTION 5: FIREFIGHTING MEASURES**

**5.1 Extinguishing media**

**Suitable extinguishing agents**

Dry chemical or foam. Sand or earth are suitable in small fires. Heavy foam and water mist only for professional firefighters.

**Unsuitable extinguishing agents**

Do not use high pressure water jets for fire extinction.

**5.2 Special hazards arising from the substance or mixture**

Flammable liquid and vapour. Explosion risk due to pressure increase if product containers or tanks are subjected to fire.

Toxic or harmful gases may be formed (complex mixtures of airborne particles, gases (smoke), carbon monoxide, oxides of sulfur, organic and inorganic compounds). Carbon dioxide may be formed by incomplete burning. The product floats in water and may ignite there.

**5.3 Advice for firefighters**

Use full protective clothing and a self-contained breathing apparatus. Cool product containers and tanks near the fire with water spray from a sufficiently safe distance. Prevent entry of extinguishing media into waterways.

**SECTION 6: ACCIDENTAL RELEASE MEASURES**

**6.1 Personal precautions, protective equipment and emergency procedures**

Evacuate people upwind from the spill area. Keep unnecessary and unprotected personnel from entering. Remove all ignition sources. Stop the leak if it can be done safely. Ensure effective ventilation at the leak site. The fumes are heavier than air, and may spread along ground.

Avoid contact with skin and breathing of oil mist. Use appropriate personal protection. Take precautionary measures (e.g. earthing) against static discharges.

**6.2 Environmental precautions**

**MATERIAL SAFETY DATA SHEET**

**NEOT Diesel -10/-20, NEOT Diesel -10/-20 Premium, NEOT Diesel -25/-35, NEOT Diesel -25/-35 Premium, NEOT Diesel -30/-38, NEOT Diesel -30/-38 Premium**

**Date:** 01.01.2019

**Former date:** 19.03.2018

Prevent spill from spreading and entry into sewers, soil and waterways. . Liquid product must be contained before it contaminates sewers, soil and waterways. If the product contaminates soil, watercourses or drainage systems, inform the local authorities.

**6.3 Methods and material for containment and cleaning up**

Immediately start clean-up of the liquid product and contaminated soil. The liquid is to be collected by pumping; small volumes can be absorbed with inert materials (e.g. sand, diatomaceous earth, commercial absorbent) and collected in tightly closable containers for proper disposal. Pay attention to the fire and health hazards caused by the product. If possible, extensive leaks into water bodies should be limited by floating booms or other mechanical means. Use of dispersants should be co-ordinated with an expert; where appropriate, local authorities must approve their use.

**6.4 Reference to other sections**

Safe handling: see section 7  
Personal protection equipment: see section 8  
Disposal: see section 13

**SECTION 7: HANDLING AND STORAGE**

**7.1 Precautions for safe handling**

Keep away from all sources of heat or ignition. Take precautionary measures (e.g. earthing) against static discharges. Concentrations in air must be kept below any lower explosive limits. Only use in closed systems or ensure adequate ventilation (use process enclosures or local exhaust ventilation if necessary). Avoid evaporation of the product during handling and transfers. Avoid inhalation of vapours and contact with skin, eyes or clothing. Wear appropriate personal protective equipment. Wash hands after handling the product. Do not eat, drink or smoke during handling. During tank operations follow special instructions (risk of oxygen displacement, ethers and hydrocarbons).

**7.2 Conditions for safe storage, including any incompatibilities**

Store in containers and areas suitable for the storage of combustible liquids. Small product batches are stored in tightly sealed containers impermeable to hydrocarbons. Recommended container materials or coatings: mild steel, stainless steel Do not store in unmarked containers or vessels. Store away from all sources of heat or ignition and food and drink. Use appropriate protective structures, such as collecting pools, loading/unloading station surfacing and sewerage systems to prevent leakage into the environment.

**7.3 Specific end use(s)**

None reported.

**SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**

**8.1 Control parameters**

**National occupational exposure limit values**

Oil mist\* 5 mg/m<sup>3</sup> (8 h) – HTP 2014/FIN

**Other limit values**

Individual limit values can be applied for hydrocarbons.

\*Occupational exposure monitoring method: SFS-EN 689, NIOSH Method 5026

**DNEL**

Workers:

Fuels, diesel, Inhalation, acute: 4300 mg/m<sup>3</sup> /15 min, oil mist (Short term exposure, systematic effects)

**MATERIAL SAFETY DATA SHEET****NEOT Diesel -10/-20, NEOT Diesel -10/-20 Premium, NEOT Diesel -25/-35, NEOT Diesel -25/-35 Premium, NEOT Diesel -30/-38, NEOT Diesel -30/-38 Premium****Date:** 01.01.2019**Former date:** 19.03.2018

Fuels, diesel, Inhalation, chronic: 68 mg/m<sup>3</sup> /8 h, oil mist, and skin, chronic: 2.9 mg/kg bw /8 h (Long term exposure, systematic effects).

Renewable hydrocarbons (diesel type fraction, EC-no: 700-916-7), Inhalation, chronic: 51.1 mg/m<sup>3</sup> and skin, chronic: 5.7 mg/m<sup>3</sup> (Long term exposure, systematic effects).

Renewable hydrocarbons (diesel type fraction, EC-no: 618-882-6 / 700-571-2), Inhalation, chronic: 147 mg/m<sup>3</sup> /day, and skin, chronic: 42 mg/kg bw /day (Long term exposure, systematic effects).

General population exposed via the environment:

Fuels, diesel, Inhalation, acute: 2600 mg/m<sup>3</sup> /15 min, oil mist (Short term exposure, systematic effects)

Fuels, diesel, Inhalation, chronic: 20 mg/m<sup>3</sup> /24 h, oil mist, and skin, chronic: 1.3 mg/kg bw /24 h (Long term exposure, systematic effects).

Renewable hydrocarbons (diesel type fraction, EC-no: 700-916-7), Inhalation, chronic: 12.9 mg/m<sup>3</sup> , and skin, chronic: 2.9 mg/kg bw / day (Long term exposure, systematic effects).

Renewable hydrocarbons (diesel type fraction, EC-no: 618-882-6 / 700-571-2), Inhalation, chronic: 94 mg/m<sup>3</sup> , and skin, chronic: 18 mg/kg bw / day (Long term exposure, systematic effects).

**PNEC**

Renewable hydrocarbons (diesel type fraction, EC-no: 700-916-7):

PNEC aqua (freshwater and marine water): 0.56 µg/L to 770 µg/L. The overall range (all representative components of the substance) estimated with the PETRORISK tool.

PNEC sediment (freshwater and marine water): 0.29 mg/kg ww to 73000 mg/kg ww. The overall range (all representative components of the substance) estimated with the PETRORISK tool.

PNEC STP: 8.4 µg/L to 12 000 µg/L. The overall range (all representative components of the substance) estimated with the PETRORISK tool.

PNEC soil: 0.12 mg/kg ww to 29000 mg/kg ww. The overall range (all representative components of the substance) estimated with the PETRORISK tool.

---

**8.2 Exposure controls**

---

**Appropriate engineering controls**

Handle the product in closed systems or provide sufficient ventilation. Use process enclosures or local exhaust ventilation and personal protection if necessary. Handle with proper personal and process safety. In confined space works use special controls (risk of low oxygen level and hydrocarbons).

**Eye/face protection**

Use tight-fitting safety goggles if splashing may occur or aerosol is formed. Use a face shield if necessary.

**Skin protection**

Wear appropriate antistatic protective clothing to prevent skin contact. If splashes may occur, wear chemical resistant gloves, shoes and apron.

**Hand protection**

Wear appropriate chemical-resistant, impervious protective gloves, e.g. of nitrile rubber, neoprene, PVC or Viton™. Protection index: 6 (breakthrough time > 480 min, EN374). Change protective gloves regularly in order to avoid penetration problems.

**Respiratory protection**

Filter device/Half mask/combined organic gas and vapour and particle filter (type A2-P3).

**MATERIAL SAFETY DATA SHEET**
**NEOT Diesel -10/-20, NEOT Diesel -10/-20 Premium, NEOT Diesel -25/-35, NEOT Diesel -25/-35 Premium, NEOT Diesel -30/-38, NEOT Diesel -30/-38 Premium**
**Date:** 01.01.2019

**Former date:** 19.03.2018

The use of filter devices should be limited to max. 2 hrs per day. Filter devices must not be used when oxygen levels are low (< 19 vol.-%). The filter has a limited lifetime and must be changed sufficiently often. If significant amounts of mist or vapour form, use supplied-air respirator. Use respiratory protection according to EN140 and EN141.

**Environmental exposure controls**

Prevent entry into sewers or the environment. Precautions must be taken against leakages by constructing collecting pools and sewerage systems as well as by surfacing the loading and unloading stations.

**SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**
**9.1 Information on basic physical and chemical properties**

<b>Appearance</b>	Clear or yellowish, bright liquid.
<b>Odour</b>	Mild scent of hydrocarbons.
<b>Odour threshold</b>	Unknown.
<b>pH</b>	Not applicable.
<b>Melting point/freezing point</b>	Cloud point
<b>Initial boiling point and boiling range</b>	150–380 °C (EN ISO 3405)
<b>Flash point</b>	> 55 °C (EN ISO 2719)
<b>Evaporation rate</b>	Unknown.
<b>Flammability (solid, gas)</b>	Unknown.
<b>Upper/lower flammability or explosive limits</b>	Upper: 6 vol-%, lower: 0.5 vol-% (estimated)
<b>Vapour pressure</b>	< 1 kPa (38 °C, estimated)
<b>Vapour density</b>	Unknown.
<b>Relative density</b>	0.8 - 0.85 (water = 1)(EN ISO 12185)
<b>Solubility(ies)</b>	Slightly soluble in water
<b>Partition coefficient: n-octanol/water</b>	log K <sub>ow</sub> 3 – above 6
<b>Auto-ignition temperature</b>	ca. 210-220 °C (estimated)
<b>Decomposition temperature</b>	Unknown.
<b>Viscosity</b>	2.0-4.5 mm <sup>2</sup> /s (40 °C) (DIN EN ISO 3104)

**MATERIAL SAFETY DATA SHEET**

**NEOT Diesel -10/-20, NEOT Diesel -10/-20 Premium, NEOT Diesel -25/-35, NEOT Diesel -25/-35 Premium, NEOT Diesel -30/-38, NEOT Diesel -30/-38 Premium**

**Date:** 01.01.2019

**Former date:** 19.03.2018

<b>Explosive properties</b>	Not classified as explosive.
<b>Oxidising properties</b>	Not classified as oxidising.

**9.2 Other information**

None reported.

**SECTION 10: STABILITY AND REACTIVITY**

**10.1 Reactivity**

Not reactive under normal use and storage conditions.

**10.2 Chemical stability**

Chemically stable under normal storage conditions.

**10.3 Possibility of hazardous reactions**

None known.

**10.4 Conditions to avoid**

Keep away from heat and ignition sources.

**10.5 Incompatible materials**

Oxidising agents.

**10.6 Hazardous decomposition products**

None known.

**SECTION 11: TOXICOLOGICAL INFORMATION**

**11.1 Information on toxicological effects**

**Acute toxicity**

Harmful if inhaled.

Fuels, diesel:

LD50 (oral, rat) > 5000 mg/kg (OECD 401, 420)

LD50 (dermal, rabbit) = 4300 mg/kg (OECD 434)

LC50 (inhaled, 4 h, rat) = 3.6 - 5.4 mg/L (OECD 403)

Distillates (Fischer-Tropsch) C8-26 branched and linear:

LD50, oral, rat > 5,000 mg/kg

LD50, dermal, rabbit > 2,000 mg/kg

Renewable hydrocarbons (diesel type fraction, EC-no: 700-916-7):

LD50 (oral, rat) > 2000 mg/kg bw (OECD 420)

LC50 (inhaled, 8 h, rat) = 23400 mg/m<sup>3</sup>

LD50 (dermal, mouse) 40000 mg/kg bw (OECD 402)

Renewable hydrocarbons (diesel type fraction, EC-no: 618-882-6 / 700-571-2):

LD50 (oral, rat) > 2000 mg/kg (EC B1 tris)

LD50 (dermal, rat) > 2000 mg/kg (EC B3)



**MATERIAL SAFETY DATA SHEET****NEOT Diesel -10/-20, NEOT Diesel -10/-20 Premium, NEOT Diesel -25/-35, NEOT Diesel -25/-35 Premium, NEOT Diesel -30/-38, NEOT Diesel -30/-38 Premium**

Date: 01.01.2019

Former date: 19.03.2018

**Skin corrosion/irritation**

Irritates skin. Prolonged or repeated contact may cause dryness or irritation of the skin. Vapours and mist may irritate the eyes and respiratory tract.

**Respiratory or skin sensitisation**

The product is not classified as a respiratory or skin sensitiser.

**Germ cell mutagenicity, carcinogenicity and reproductive toxicity**

Fuels, diesel:

The product is suspected of causing cancer (hydrocracked gas-oil fractions). In animal studies (in vitro), genotoxic effects have been observed in bacteria and mouse lymphocytes but the effects were not observed in in vivo studies.(OECD 471, 475). Not classifiable as teratogenic (OECD 414).

Renewable hydrocarbons (diesel type fraction, EC-no: 618-882-6 / 700-571-2):

No mutagenic effects were observed in in vitro studies (EC B10, B13/14, B17).

The product is not classified as a reproductive toxicant (OECD 416).

**STOT-single exposure**

The product is not classified as toxic to specific target organs. However, oil mist may irritate airways.

**STOT-repeated exposure**

Fuels, diesel:

The product is classified as toxic to specific target organs in case of repeated exposure. May cause damage to organs through prolonged or repeated exposure. Target organs: blood, thymus and liver.

Renewable hydrocarbons (diesel type fraction, EC-no: 700-916-7):

Based on the data on similar fossil fuels causing dermatitis and neurotoxicity the substance is classified for STOT RE 2.

Renewable hydrocarbons (diesel type fraction, EC-no: 618-882-6 / 700-571-2):

No known effects (OECD 408)

**Aspiration hazard**

The product may be fatal if swallowed and enters airways. May cause fatal chemical pneumonia.

**Other information**

Ingestion may cause irritation of the gastrointestinal tract.

**SECTION 12: ECOLOGICAL INFORMATION****12.1 Toxicity**

Toxic to aquatic life with long lasting effects.

**Acute toxicity**

**MATERIAL SAFETY DATA SHEET****NEOT Diesel -10/-20, NEOT Diesel -10/-20 Premium, NEOT Diesel -25/-35, NEOT Diesel -25/-35 Premium, NEOT Diesel -30/-38, NEOT Diesel -30/-38 Premium****Date:** 01.01.2019**Former date:** 19.03.2018

Fuels, diesel:

Fish: LL50/96 h = 21 mg/L, NOEL/96 h = 10 mg/L; WAF (OECD 203, EC C.1)

Daphnia: EL50/48 h = 68 mg/L; NOEL/48 h = 47 mg/L; WAF (OECD 202, EC C.2)

Algae: EbL/72 h = 10 mg/L; NOEL/48 h = 3 mg/L; NOEL/72 h = 1 mg/L; WAF (OECD 201, EC C.3)

Distillates (Fischer-Tropsch) C8-26 branched and linear:

Fish: LL50/96 h &gt;100 mg/l

Daphnia: EL50/48 h &gt;100 mg/l

Algae: EbL/72 h &gt;100 mg/l

Renewable hydrocarbons (diesel type fraction, EC-no: 700-916-7):

Fish: LL50/96 h 31 mg/L (OECD 203)

Daphnia: EL50/48 h 68 mg/L (OECD 202)

Algae: EL50/72 h &gt; 100 mg/L (OECD 201)

Renewable hydrocarbons (diesel type fraction, EC-no: 618-882-6 / 700-571-2):

Fish: LL50/96 h &gt; 1000 mg/L (WAF) (OECD 203)

Daphnia: EL50/ 48 h &gt; 100 mg/L (WAF) (OECD 202)

Algae: EL50/72 h &gt; 100 mg/L (WAF) (OECD 201)

**Long term toxicity**

Fuels, diesel:

Fish: NOEL/14 d = 0.08 mg/L (QSAR)

Daphnia: NOEL/21 d = 0.2 mg/L (QSAR)

Distillates (Fischer-Tropsch) C8-26 branched and linear:

NOEL, fish: &gt; 100 mg/l (14 days)

NOEL, shellfish: &gt;10 - &lt;100 mg/l (21 days)

Renewable hydrocarbons (diesel type fraction, EC-no: 700-916-7 / 700-571-2):

Unknown

Renewable hydrocarbons (diesel type fraction, EC-no: 618-882-6):

Daphnia: NOEC/21 d = 1 mg/L; LOEC/21 d = 3.2 mg/L; WAF (OECD 211)

sediment: NOEC/10 d = 373 mg/kg; LOEC/10 d = 1165 mg/kg; LC50/10 d = 1200 mg/kg (OSPAR Protocols, Part A: Sediment Bioassay, 2005)

**Toxicity to micro-organisms**

Fuels, diesel: EL50/40 h &gt; 1000 mg/L; NOEL/40 h = 3.22 mg/L (QSAR)

Renewable hydrocarbons (diesel type fraction, EC-no: 700-916-7): EL10 (3 h): 39.25 mg/l (OECD 209; GLP)

Renewable hydrocarbons (diesel type fraction, EC-no: 618-882-6): EC50/30 min &gt; 1000 mg/L; EC50/3 h &gt; 1000 mg/L (OECD 209).

---

**12.2 Persistence and degradability**

---

**Biodegradability**

Readily biodegradable. (Fuels, diesel: OECD 301F, Renewable hydrocarbons (diesel type fraction, EC-no: 618-882-6/ 700-571-2): OECD 301B)

Renewable hydrocarbons (diesel type fraction, EC-no: 700-916-7): No biodegradable. (28 days biodeg.-% 33; OECD 301B; GLP).

**MATERIAL SAFETY DATA SHEET**

**NEOT Diesel -10/-20, NEOT Diesel -10/-20 Premium, NEOT Diesel -25/-35, NEOT Diesel -25/-35 Premium, NEOT Diesel -30/-38, NEOT Diesel -30/-38 Premium**

**Date:** 01.01.2019

**Former date:** 19.03.2018

**Chemical degradability**

Does not hydrolyze in water. Gas-oil hydrocarbons may also degrade photochemically in surface water. Volatile hydrocarbons undergo atmospheric degradation.

**12.3 Bioaccumulative potential**

The product may be bioaccumulative (log  $K_{ow}$  > 3).

**12.4 Mobility in soil**

The product is slightly water-soluble and evaporates slowly from water and soil surfaces. May leach through soil and pollute groundwater. Petroleum and gas-oil hydrocarbons can be adsorbed onto organic material in soil or sediment. In anaerobic conditions, degradation is extremely slow.

**12.5 Results of PBT and vPvB assessment**

The product does not contain components considered persistent, bioaccumulative or toxic (PBT). The product does not contain components considered very persistent or very bioaccumulative (vPvB).

**12.6 Other adverse effects**

The product may stick to organisms and be lethally harmful. The product forms a film on the water surface, which can affect the oxygen balance and damage the organisms.

**SECTION 13: DISPOSAL CONSIDERATIONS**

**13.1 Waste treatment methods**

Hazardous waste. Dispose of in accordance with local and national regulation. When handling waste, observe the hazards and take all necessary precautionary measures. Observe also labelling and information requirements.

**13.2 Waste from residues/unused products**

Empty containers may contain flammable remnants of product. Dispose of empty containers for recovery, recycling or waste.

**SECTION 14: TRANSPORT INFORMATION**

**14.1 UN-number**

1202

**14.2 UN proper shipping name**

DIESEL FUEL

**14.3 Transport hazard class(es)**

3

**14.4 Packing group**

III

**14.5 Environmental hazards**

Marine Pollutant

**14.6 Special precautions for user**

No special precautions.

**14.7 Transport in bulk according to MARPOL73/78 and the IBC Code**

**MATERIAL SAFETY DATA SHEET**

**NEOT Diesel -10/-20, NEOT Diesel -10/-20 Premium, NEOT Diesel -25/-35, NEOT Diesel -25/-35 Premium, NEOT Diesel -30/-38, NEOT Diesel -30/-38 Premium**

**Date:** 01.01.2019

**Former date:** 19.03.2018

Bulk (MARPOL 73/78, Annex I): Energy-rich fuels

This cargo is considered an Energy-rich fuel and effective 1 January 2019 should be carried subject to Annex I of MARPOL, see Annex 12 of MEPC.2/Circ.24.

Please also refer to MEPC.1/Circ.879 -GUIDELINES FOR THE CARRIAGE OF ENERGY-RICH FUELS AND THEIR BLENDS.

**SECTION 15: REGULATORY INFORMATION**

**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

MSDS compiled according to Regulations (EC) No 1907/2006 REACH and amendment (EU) No 453/2010.

**15.2 Chemical safety assessment**

Chemical safety assessment has been performed for the ingredients.

**SECTION 16: OTHER INFORMATION**

**16.1 Changes to the previous version**

Section 14 Transport information

**16.2 Glossary of abbreviations**

CLP: REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006

DSD: Directive 67/548/EEC - classification, packaging and labelling of dangerous substances

DPD: Directive 1999/45/EC - classification, packaging and labelling of dangerous preparations

HTP: Concentrations known to be hazardous

DNEL: Derived no-effect level

EL50: Effective level 50 % (median effective level): loading rate of the substance which kills or immobilizes 50 % of exposed organisms

IL50: Inhibitory level 50 % (median inhibitory level): loading rate of the substance which inhibits a biological function by 50 %

LD50: Lethal dose 50 % (median lethal dose): dose of the substance which kills 50 % of exposed organisms

LL50: Lethal level 50 % (median lethal level): loading rate of the substance which kills 50 % of the exposed organisms

WAF: Water-accommodated fraction: fraction of the substance mixed into the water phase (method applied to poorly water-soluble substances)

**16.3 References**

Finnish-language MSDS for the product (7 January 2015)

**16.5 List of relevant R and H phrases**

R20 Harmful by inhalation

R38 Irritating to skin

R40 Limited evidence of a carcinogenic effect.

R65 Harmful: may cause lung damage if swallowed.

R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

H226 Flammable liquid and vapour.

**MATERIAL SAFETY DATA SHEET**

**NEOT Diesel -10/-20, NEOT Diesel -10/-20 Premium, NEOT Diesel -25/-35, NEOT Diesel -25/-35 Premium,  
NEOT Diesel -30/-38, NEOT Diesel -30/-38 Premium**

**Date:** 01.01.2019

**Former date:** 19.03.2018

---

H332	Harmful if inhaled.
H315	Causes skin irritation.
H304	May be fatal if swallowed and enters airways.
H351	Suspected of causing cancer.
H373	May cause damage to organs through prolonged or repeated exposure.
H411	Toxic to aquatic life with long lasting effects.

**16.7 Restrictions on use**

Identified uses:

Distribution of the substance (SU3; PROC: 4, 8a, 8b, 9, 15; ERC: 1, 2, 3, 4, 5, 6a, 6b, 6c, 6d, 7)

Use as a fuel

Industrial (SU 3; PROC: 1, 2, 3, 8a, 8b, 16; ERC: 7)

Professional (SU 22; PROC: 1, 2, 3, 8a, 8b, 16; ERC: 9a, 9b)

Consumers (SU 21; PC 13; ERC: 9a, 9b)

Use of substance in Explosives Manufacture and Use – Professional (SU22; PROC: 1, 3, 5, 8a, 8b; ERC: 8e)

Use in Road and Construction Applications - Professional (SU22; PROC: 8a, 8b, 9, 10, 11, 13; ERC: 8d, 8f)

DO NOT TRY TO SUCK DIESEL OIL USING YOUR MOUTH.

**16.8 Further information**

NEOT Oy, Tuotelaatu, +358 10 402 7001, tuotelaatu@neot.fi

**MATERIAL SAFETY DATA SHEET**
**NEOT Diesel -10/-20, NEOT Diesel -10/-20 Premium, NEOT Diesel -25/-35, NEOT Diesel -25/-35 Premium, NEOT Diesel -30/-38, NEOT Diesel -30/-38 Premium**
**Date:** 01.01.2019

**Former date:** 19.03.2018

**ANNEX EXTENDED MATERIAL SAFETY DATA SHEET**
**Exposure scenarios 1-6**
**AS1: Distribution of Substance - Industrial**
**1. Title**

Use of descriptor	Sector(s) of Use: Industrial (SU3).
	Process Categories: PROC 1, PROC 2, PROC 3, PROC 4, PROC 8a, PROC 8b, PROC 9, PROC 15
	Environmental Release Categories (ERC): 1, 2, 3, 4, 5, 6a, 6b, 6c, 7
	Specific Environmental Release Category: ESVOC SpERC 1.1b.v1
Processes, Tasks and Activities Covered	Bulk loading (including marine vessel/barge, rail/road car and IBC loading) and repacking (including drums and small packs) of substance, including its sampling, storage, unloading, maintenance and associated laboratory activities.

**2. Operational conditions and risk management measures**
**2.1. Control of worker exposure**

<b>Product characteristics</b>
<b>Physical form of product:</b> Liquid With potential for aerosol generation <b>Vapour pressure (kPa):</b> Liquid, vapour pressure <0.5 kPa at STP [OC3].
<b>Concentration of substance in product</b>
Covers percentage substance in the product up to 100 % (unless stated differently) [G13].
<b>Frequency and duration of use</b>
Covers daily exposures up to 8 hours (unless stated differently) [G2].
<b>Other operational conditions affecting worker exposure</b>
Assumes use at not more than 20 °C above ambient temperature, unless stated differently [G15]. Assumes a good basic standard of occupational hygiene is implemented [G1].
<b>Specific Risk Management Measures and Operational Conditions</b>
<b>General measures applicable to all activities [CS135]</b>
Control any potential exposure using measures such as contained systems, properly designed and maintained facilities and a good standard of general ventilation. Drain down systems and transfer lines prior to breaking containment. Drain down and flush equipment where possible prior to maintenance. Where there is potential for exposure: Ensure relevant staff are informed of exposure potential and aware of basic actions to minimise exposures; ensure suitable personal protective equipment is available; clear up spills and dispose of waste in accordance with regulatory requirements; monitor effectiveness of control measures; provide regular health surveillance as appropriate; identify and implement corrective actions [G25].

**MATERIAL SAFETY DATA SHEET**
**NEOT Diesel -10/-20, NEOT Diesel -10/-20 Premium, NEOT Diesel -25/-35, NEOT Diesel -25/-35 Premium, NEOT Diesel -30/-38, NEOT Diesel -30/-38 Premium**
**Date:** 01.01.2019

**Former date:** 19.03.2018

<b>General measures (skin irritants) [G19]</b>
Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off skin contamination immediately. Provide basic employee training to prevent / minimise exposures and to report any skin effects that may develop [E3].
<b>General exposures (closed systems) [CS15]</b>
Handle substance within a closed system [E47].
<b>General exposures (open systems) [CS16]</b>
Wear suitable gloves tested to EN374 [PPE15].
<b>Process sampling [CS2]</b>
No other specific measures identified [E120].
<b>Laboratory activities [CS36]</b>
No other specific measures identified [E120].
<b>Bulk closed loading and unloading [CS501]</b>
Handle substance within a closed system [E47]. Wear suitable gloves tested to EN374 [PPE15].
<b>Bulk open loading and unloading [CS503]</b>
Wear suitable gloves tested to EN374 [PPE15].
<b>Drum and small pack filling [CS6]</b>
Wear suitable gloves tested to EN374 [PPE15].
<b>Equipment cleaning and maintenance [CS39]</b>
Drain down system prior to equipment break-in or maintenance [E65]. Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training [PPE16].
<b>Storage [CS67]</b>
Handle substance within a closed system [E84].

**2.2. Control of environmental exposure**

<b>Product characteristics</b>
Substance is complex UVCB [PrC3]. Predominantly hydrophobic [PrC4a].
<b>Amounts used</b>
Fraction of EU tonnage used in region: 0.1
Regional tonnage: 2.8 e <sup>7</sup> tonnes per year
Fraction of Regional tonnage used locally: 0.002
Annual site tonnage: 5.6 e <sup>4</sup> tonnes per year
Maximum daily site tonnage: 0.19 kilotonnes per day
<b>Frequency and duration of use</b>
Continuous release [FD2].
Emission days per year: 300
<b>Environmental factors not influenced by risk management</b>
Local freshwater dilution fraction: 10

**MATERIAL SAFETY DATA SHEET**
**NEOT Diesel -10/-20, NEOT Diesel -10/-20 Premium, NEOT Diesel -25/-35, NEOT Diesel -25/-35 Premium, NEOT Diesel -30/-38, NEOT Diesel -30/-38 Premium**
**Date:** 01.01.2019

**Former date:** 19.03.2018

Local marine dilution fraction: 100
<b>Other Operational Conditions of use affecting environmental exposure</b>
Release fraction to air from process (initial release prior to RMM): 0.001 Release fraction to wastewater from process (initial release prior to RMM): 0.000001 Release fraction to soil from process (initial release prior to RMM): 0.00001
<b>Technical condition and measures at process level (source) to prevent release</b>
TCS 1: Common practices vary across sites thus conservative process release estimates used.
<b>Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil</b>
TCR1j: Risk from environmental exposure is driven by human via indirect exposure (primarily ingestion). TCR14: Prevent discharge of undissolved substance to or recover from onsite wastewater. TCR6: No wastewater treatment required. Treat air emission to provide a typical removal efficiency of 90 %. Treat onsite wastewater (prior to receiving water discharge) to provide the required removal efficiency $\geq 0$ %. If discharging to domestic sewage treatment plant, provide the required onsite wastewater removal efficiency of $\geq 0$ %.
<b>Organizational measures to prevent / limit release from site</b>
Prevent discharge of undissolved substance to or recover from wastewater [OMS1]. Do not apply industrial sludge to natural soils [OMS2]. Sludge should be incinerated, contained or reclaimed [OMS3].
<b>Conditions and measures related to municipal sewage treatment plant</b>
Estimated substance removal from wastewater via domestic sewage treatment 94.1 %.
Total efficiency of removal from wastewater after onsite and offsite (domestic treatment plant) RMMs 94.1 %.
Maximum allowable site tonnage ( $M_{Safe}$ ) based on release following total wastewater treatment removal 2.9 kilotonnes per day.
Assumed domestic sewage treatment plant flow 2000 m <sup>3</sup> /day.
<b>Conditions and measures related to external treatment of waste for disposal</b>
ETW3: External treatment and disposal of waste should comply with applicable regulations.
<b>Conditions and measures related to external recovery of waste</b>
ERW1: External recovery and recycling of waste should comply with applicable regulations.

### 3. Exposure estimation

#### 3.1 Health

The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated [G21].

#### 3.2 Environment

The Hydrocarbon Block Method has been used to calculate environmental exposure with Petrorisk model [EE2].



**MATERIAL SAFETY DATA SHEET**

**NEOT Diesel -10/-20, NEOT Diesel -10/-20 Premium, NEOT Diesel -25/-35, NEOT Diesel -25/-35 Premium, NEOT Diesel -30/-38, NEOT Diesel -30/-38 Premium**

**Date:** 01.01.2019

**Former date:** 19.03.2018

## **4. Guidance to check compliance with the exposure scenario**

### **4.1 Health**

Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented [G22]. Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels [G23]. Available hazard data do not enable the derivation of a DNEL for dermal irritant effects [G32]. Available hazard data do not support the need for a DNEL to be established for other health effects [G36]. Risk Management Measures are based on qualitative risk characterisation [G37].

### **4.2 Environment**

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures [DSU1]. Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination [DSU2]. Required removal efficiency for air can be achieved using onsite technologies, either alone or in combination [DSU3]. Further details on scaling and control technologies are provided in SpERC. Factsheet (<http://cefic.org/en/reach-for-industries-libraries.html>) [DSU4].

**MATERIAL SAFETY DATA SHEET**
**NEOT Diesel -10/-20, NEOT Diesel -10/-20 Premium, NEOT Diesel -25/-35, NEOT Diesel -25/-35 Premium, NEOT Diesel -30/-38, NEOT Diesel -30/-38 Premium**
**Date:** 01.01.2019

**Former date:** 19.03.2018

## AS2: Use as a Fuel - Industrial

### 1. Title

Use of descriptor	Sector(s) of Use: Industrial (SU3).
	Process Categories PROC: PROC1, PROC2, PROC3, PROC8a, PROC8b, PROC16
	Environmental Release Categories (ERC): 7  Specific Environmental Release Category: ESVOC SpERC 7.12a.v1
Processes, Tasks and Activities Covered	Covers the use as a fuel (or fuel additives and additive components) and includes activities associated with its transfer, use, equipment maintenance and handling of waste.

## 2. Operational conditions and risk management measures

### 2.1. Control of worker exposure

<b>Product characteristics</b>
<b>Physical form of product:</b> Liquid With potential for aerosol generation [CS138] <b>Vapour pressure (kPa):</b> Liquid, vapour pressure <0.5 kPa at STP [OC3].
<b>Concentration of substance in product</b>
Covers percentage substance in the product up to 100 % (unless stated differently) [G13].
<b>Frequency and duration of use</b>
Covers daily exposures up to 8 hours (unless stated differently) [G2].
<b>Other operational conditions affecting worker exposure</b>
Assumes use at not more than 20 °C above ambient temperature, unless stated differently [G15]. Assumes a good basic standard of occupational hygiene is implemented [G1].
<b>Specific Risk Management Measures and Operational Conditions</b>
<b>General measures applicable to all activities [CS135]</b>
Control any potential exposure using measures such as contained systems, properly designed and maintained facilities and a good standard of general ventilation. Drain down systems and transfer lines prior to breaking containment. Drain down and flush equipment where possible prior to maintenance. Where there is potential for exposure: Ensure relevant staff are informed of exposure potential and aware of basic actions to minimise exposures; ensure suitable personal protective equipment is available; clear up spills and dispose of waste in accordance with regulatory requirements; monitor effectiveness of control measures; provide regular health surveillance as appropriate; identify and implement corrective actions [G25].
<b>General measures (skin irritants) [G19]</b>
Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off skin contamination immediately. Provide basic employee training to prevent / minimise exposures and to report any skin effects that may develop [E3].

**MATERIAL SAFETY DATA SHEET**
**NEOT Diesel -10/-20, NEOT Diesel -10/-20 Premium, NEOT Diesel -25/-35, NEOT Diesel -25/-35 Premium, NEOT Diesel -30/-38, NEOT Diesel -30/-38 Premium**
**Date:** 01.01.2019

**Former date:** 19.03.2018

<b>Use as a fuel (closed systems) [GEST_12I, CS107]</b>
No other specific measures identified [E120].
<b>Bulk transfers [CS14]</b>
Wear suitable gloves tested to EN374 [PPE15].
<b>Drum/batch transfers [CS8]</b>
Wear suitable gloves tested to EN374 [PPE15].
<b>Equipment cleaning and maintenance [CS39]</b>
Drain down system prior to equipment break-in or maintenance [E65]. Wear chemically resistant gloves (tested to EN374) in
<b>Storage [CS67]</b>
Handle substance within a closed system [E84].

**2.2. Control of environmental exposure**

<b>Product characteristics</b>
Substance is complex UVCB [PrC3]. Predominantly hydrophobic [PrC4a].
<b>Amounts used</b>
Fraction of EU tonnage used in region: 0.1
Regional tonnage: 4500 kilotonnes per year
Fraction of Regional tonnage used locally: 0.34
Annual site tonnage: 1500 kilotonnes per year
Maximum daily site tonnage: 5 kilotonnes per day
<b>Frequency and duration of use</b>
Continuous release [FD2].
Emission days per year: 300
<b>Environmental factors not influenced by risk management</b>
Local freshwater dilution fraction: 10
Local marine dilution fraction: 100
<b>Other Operational Conditions of use affecting environmental exposure</b>
Release fraction to air from process (initial release prior to RMM): 0.005
Release fraction to wastewater from process (initial release prior to RMM): 0.00001
Release fraction to soil from process (initial release prior to RMM): 0
<b>Technical condition and measures at process level (source) to prevent release</b>
TCS 1: Common practices vary across sites thus conservative process release estimates used.
<b>Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil</b>
TCR1b: Risk from environmental exposure is driven by freshwater sediment
TCR9: If discharging to domestic sewage treatment plant, no onsite wastewater treatment required.
Treat air emission to provide a typical removal efficiency of 95 %.
Treat onsite wastewater (prior to receiving water discharge) to provide the required removal efficiency $\geq 97.7$ %.
If discharging to domestic sewage treatment plant, provide the required onsite wastewater removal efficiency of $\geq 60.4$ %.

**MATERIAL SAFETY DATA SHEET**

**NEOT Diesel -10/-20, NEOT Diesel -10/-20 Premium, NEOT Diesel -25/-35, NEOT Diesel -25/-35 Premium, NEOT Diesel -30/-38, NEOT Diesel -30/-38 Premium**

**Date:** 01.01.2019

**Former date:** 19.03.2018

<b>Organizational measures to prevent / limit release from site</b>
Prevent discharge of undissolved substance to or recover from wastewater [OMS1]. Do not apply industrial sludge to natural soils [OMS2]. Sludge should be incinerated, contained or reclaimed [OMS3].
<b>Conditions and measures related to municipal sewage treatment plant</b>
Estimated substance removal from wastewater via domestic sewage treatment 94.1 %.
Total efficiency of removal from wastewater after onsite and offsite (domestic treatment plant) RMMs 97.7 %.
Maximum allowable site tonnage (M <sub>safe</sub> ) based on release following total wastewater treatment removal 5000 tonnes per day.
Assumed domestic sewage treatment plant flow 2000 m <sup>3</sup> /day.
<b>Conditions and measures related to external treatment of waste for disposal</b>
ETW1: Combustion emissions limited by required exhaust emission controls. ETW2: Combustion emissions considered in regional exposure assessment.
<b>Conditions and measures related to external recovery of waste</b>
ERW1: External recovery and recycling of waste should comply with applicable regulations.

### 3. Exposure estimation

#### 3.1 Health

The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated [G21].

#### 3.2 Environment

The Hydrocarbon Block Method has been used to calculate environmental exposure with Petrorisk model [EE2].

### 4. Guidance to check compliance with the exposure scenario

#### 4.1 Health

Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented [G22].

Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels [G23].

Available hazard data do not enable the derivation of a DNEL for dermal irritant effects [G32]. Available hazard data do not support the need for a DNEL to be established for other health effects [G36]. Risk Management Measures are based on qualitative risk characterisation [G37].

#### 4.2 Environment

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures [DSU1]. Required removal efficiency for

**MATERIAL SAFETY DATA SHEET**

**NEOT Diesel -10/-20, NEOT Diesel -10/-20 Premium, NEOT Diesel -25/-35, NEOT Diesel -25/-35 Premium,  
NEOT Diesel -30/-38, NEOT Diesel -30/-38 Premium**

**Date:** 01.01.2019

**Former date:** 19.03.2018

---

wastewater can be achieved using onsite/offsite technologies, either alone or in combination [DSU2]. Required removal efficiency for air can be achieved using onsite technologies, either alone or in combination [DSU3]. Further details on scaling and control technologies are provided in SpERC. Factsheet (<http://cefic.org/en/reach-for-industries-libraries.html>) [DSU4].

**MATERIAL SAFETY DATA SHEET**
**NEOT Diesel -10/-20, NEOT Diesel -10/-20 Premium, NEOT Diesel -25/-35, NEOT Diesel -25/-35 Premium, NEOT Diesel -30/-38, NEOT Diesel -30/-38 Premium**
**Date:** 01.01.2019

**Former date:** 19.03.2018

## AS3: Use as a Fuel - Professional

### 1. Title

Use of descriptor	Sector(s) of Use: Professional (SU22).
	Process Categories: PROC1, PROC2, PROC3, PROC8a, PROC8b, PROC16
	Environmental Release Categories (ERC): 9a, 9b
	Specific Environmental Release Category: ESVOC SpERC 9.12b.v1
Processes, Tasks and Activities Covered	Covers the use as a fuel (or fuel additives and additive components) and includes activities associated with its transfer, use, equipment maintenance and handling of waste.

## 2. Operational conditions and risk management measures

### 2.1. Control of worker exposure

<b>Product characteristics</b>
<b>Physical form of product:</b> Liquid. With potential for aerosol generation [CS138] <b>Vapour pressure (kPa):</b> Liquid, vapour pressure <0.5 kPa at STP [OC3].
<b>Concentration of substance in product</b>
Covers percentage substance in the product up to 100 % (unless stated differently) [G13].
<b>Frequency and duration of use</b>
Covers daily exposures up to 8 hours (unless stated differently) [G2].
<b>Other operational conditions affecting worker exposure</b>
Assumes use at not more than 20 °C above ambient temperature, unless stated differently [G15]. Assumes a good basic standard of occupational hygiene is implemented [G1].
<b>Specific Risk Management Measures and Operational Conditions</b>
<b>General measures applicable to all activities [CS135]</b>
Control any potential exposure using measures such as contained systems, properly designed and maintained facilities and a good standard of general ventilation. Drain down systems and transfer lines prior to breaking containment. Drain down and flush equipment where possible prior to maintenance. Where there is potential for exposure: Ensure relevant staff are informed of exposure potential and aware of basic actions to minimise exposures; ensure suitable personal protective equipment is available; clear up spills and dispose of waste in accordance with regulatory requirements; monitor effectiveness of control measures; provide regular health surveillance as appropriate; identify and implement corrective actions [G25].
<b>General measures (skin irritants) [G19]</b>
Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off skin contamination immediately. Provide basic employee training to prevent / minimise exposures and to report any skin effects that may develop [E3].

**MATERIAL SAFETY DATA SHEET**
**NEOT Diesel -10/-20, NEOT Diesel -10/-20 Premium, NEOT Diesel -25/-35, NEOT Diesel -25/-35 Premium, NEOT Diesel -30/-38, NEOT Diesel -30/-38 Premium**
**Date:** 01.01.2019

**Former date:** 19.03.2018

<b>Use as a fuel (closed systems) [GEST_12I, CS107]</b>
Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour) [E11] or Ensure operation is undertaken outdoors [E69].
<b>Bulk transfers [CS14]</b>
Wear suitable gloves tested to EN374 [PPE15].
<b>Drum/batch transfers [CS8]</b>
Use drum pumps or carefully pour from container [E64]. Wear suitable gloves tested to EN374 [PPE15].
<b>Refuelling activities [CS507]</b>
Wear suitable gloves tested to EN374 [PPE15].
<b>Equipment cleaning and maintenance [CS39]</b>
Drain down system prior to equipment break-in or maintenance [E65]. Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training [PPE16].
<b>Storage [CS67]</b>
Handle substance within a closed system [E84].

**2.2. Control of environmental exposure**

<b>Product characteristics</b>
Substance is complex UVCB [PrC3]. Predominantly hydrophobic [PrC4a].
<b>Amounts used</b>
Fraction of EU tonnage used in region: 0.1
Regional tonnage: 6.7 e <sup>7</sup> per year
Fraction of Regional tonnage used locally: 0.0005
Annual site tonnage: 3.3 kilotonnes per year
Maximum daily site tonnage: 9.2 tonnes per day
<b>Frequency and duration of use</b>
Continuous release [FD2].
Emission days per year: 365
<b>Environmental factors not influenced by risk management</b>
Local freshwater dilution fraction: 10
Local marine dilution fraction: 100
<b>Other Operational Conditions of use affecting environmental exposure</b>
Release fraction to air from process (initial release prior to RMM): 0.0001
Release fraction to wastewater from process (initial release prior to RMM): 0.00001
Release fraction to soil from process (initial release prior to RMM): 0,00001
<b>Technical condition and measures at process level (source) to prevent release</b>
TCS 1: Common practices vary across sites thus conservative process release estimates used.
<b>Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil</b>
TCR1j: Risk from environmental exposure is driven by human via indirect exposure (primarily ingestion).

**MATERIAL SAFETY DATA SHEET**

**NEOT Diesel -10/-20, NEOT Diesel -10/-20 Premium, NEOT Diesel -25/-35, NEOT Diesel -25/-35 Premium, NEOT Diesel -30/-38, NEOT Diesel -30/-38 Premium**

**Date:** 01.01.2019

**Former date:** 19.03.2018

TCR6: No wastewater treatment required.  
 Treat air emission to provide a typical removal efficiency of N/A.  
 Treat onsite wastewater (prior to receiving water discharge) to provide the required removal efficiency  $\geq 0\%$ .  
 If discharging to domestic sewage treatment plant, provide the required onsite wastewater removal efficiency of  $\geq 0\%$ .

**Organizational measures to prevent / limit release from site**

Prevent discharge of undissolved substance to or recover from wastewater [OMS1]. Do not apply industrial sludge to natural soils [OMS2]. Sludge should be incinerated, contained or reclaimed [OMS3].

**Conditions and measures related to municipal sewage treatment plant**

Estimated substance removal from wastewater via domestic sewage treatment 94.1 %.

Total efficiency of removal from wastewater after onsite and offsite (domestic treatment plant) RMMs 94.1 %.

Maximum allowable site tonnage ( $M_{Safe}$ ) based on release following total wastewater treatment removal 140 tonnes per day.

Assumed domestic sewage treatment plant flow 2000 m<sup>3</sup>/day.

**Conditions and measures related to external treatment of waste for disposal**

ETW1: Combustion emissions limited by required exhaust emission controls.  
 ETW2: Combustion emissions considered in regional exposure assessment.

**Conditions and measures related to external recovery of waste**

ERW1: External recovery and recycling of waste should comply with applicable regulations.

**3. Exposure estimation**

**3.1 Health**

The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated [G21].

**3.2 Environment**

The Hydrocarbon Block Method has been used to calculate environmental exposure with Petrorisk model [EE2].

**4. Guidance to check compliance with the exposure scenario**

**4.1 Health**

Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented [G22].

Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels [G23].

Available hazard data do not enable the derivation of a DNEL for dermal irritant effects [G32]. Available hazard data do not support the need for a DNEL to be established for other health effects [G36]. Risk Management Measures are based on qualitative risk characterisation [G37].



**MATERIAL SAFETY DATA SHEET**

**NEOT Diesel -10/-20, NEOT Diesel -10/-20 Premium, NEOT Diesel -25/-35, NEOT Diesel -25/-35 Premium,  
NEOT Diesel -30/-38, NEOT Diesel -30/-38 Premium**

**Date:** 01.01.2019

**Former date:** 19.03.2018

---

## **4.2 Environment**

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures [DSU1]. Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination [DSU2]. Required removal efficiency for air can be achieved using onsite technologies, either alone or in combination [DSU3]. Further details on scaling and control technologies are provided in SpERC. Factsheet (<http://cefic.org/en/reach-for-industries-libraries.html>) [DSU4].

**MATERIAL SAFETY DATA SHEET**
**NEOT Diesel -10/-20, NEOT Diesel -10/-20 Premium, NEOT Diesel -25/-35, NEOT Diesel -25/-35 Premium, NEOT Diesel -30/-38, NEOT Diesel -30/-38 Premium**
**Date:** 01.01.2019

**Former date:** 19.03.2018

**AS4: Use as a Fuel – Consumer**
**1. Title**

Use of descriptor	Sector(s) of Use: Professional (SU21).
	Process Categories: PROC13
	Environmental Release Categories (ERC): 9a, 9b  Specific Environmental Release Category: ESVOC SpERC 9.12b.v1
Processes, Tasks and Activities Covered	Covers consumer uses in fuels.

**2. Operational conditions and risk management measures**
**2.1. Control of worker exposure**

<b>Product characteristics</b>
<b>Physical form of product:</b> Liquid <b>Vapour pressure (kPa):</b> Liquid, vapour pressure > 10 kPa [OC15].
<b>Concentration of substance in product</b>
Covers percentage substance in the product up to 100 % (unless stated differently) [G13].
<b>Frequency and duration of use</b>
Unless otherwise stated, covers use amounts up to 37500 g [ConsOC2]; covers skin contact area up to 420 cm <sup>2</sup> [ConsOC5]
<b>Other operational conditions affecting worker exposure</b>
Unless otherwise stated, covers use frequency up to 0.143 times per day [ConsOC4]; covers exposure up to 2 hours per event [ConsOC14]
<b>Specific Risk Management Measures and Operational Conditions</b>
<b>PC13: Fuels- Liquid – subcategories added: Automotive Refuelling</b>
OC: Unless otherwise stated, covers concentrations up to 100 % [ConsOC1]; covers use up to 52 days/year [ConsOC3]; covers use up to 1 time/on day of use [ConsOC4]; covers skin contact area up to 210.00 cm <sup>2</sup> [ConsOC5]; for each use event, covers use amounts up to 37500 g [ConsOC2]; covers outdoor use [ConsOC12]; covers use in room size of 100 m <sup>3</sup> [ConsOC11]; for each use event, covers exposure up to 0.05 hr/event [ConsOC14];
RMM: No specific RMMs developed beyond those OCs stated [ConsRMM15]
<b>PC13: Fuels- Liquid – subcategories added: Garden Equipment - Use</b>
OC: Unless otherwise stated, covers concentrations up to 100 % [ConsOC1]; covers use up to 26 days/year [ConsOC3]; covers use up to 1 time/on day of use [ConsOC4]; for each use event, covers use amounts up to 750 g [ConsOC2]; covers outdoor use [ConsOC12]; covers use in room size of 100 m <sup>3</sup> [ConsOC11]; for each use event, covers exposure up to 2.00 hr/event [ConsOC14];
RMM: No specific RMMs developed beyond those OCs stated [ConsRMM15]
<b>PC13: Fuels- Liquid – subcategories added: Garden Equipment - Refuelling</b>

**MATERIAL SAFETY DATA SHEET**
**NEOT Diesel -10/-20, NEOT Diesel -10/-20 Premium, NEOT Diesel -25/-35, NEOT Diesel -25/-35 Premium, NEOT Diesel -30/-38, NEOT Diesel -30/-38 Premium**
**Date:** 01.01.2019

**Former date:** 19.03.2018

OC: Unless otherwise stated, covers concentrations up to 100 % [ConsOC1]; covers use up to 26 days/year [ConsOC3]; covers use up to 1 time/on day of use [ConsOC4]; covers skin contact area up to 420.00 cm<sup>2</sup> [ConsOC5]; for each use event, covers use amounts up to 750 g [ConsOC2]; Coversuse in a one car garage (34 m<sup>3</sup>) under typical ventilation [ConsOC10]; covers use in room size of 34 m<sup>3</sup> [ConsOC11]; for each use event, covers exposure up to 0.03 hr/event [ConsOC14];

RMM: No specific RMMs developed beyond those OCs stated [ConsRMM15]

**2.2. Control of environmental exposure**

<b>Product characteristics</b>
Substance is complex UVCB [PrC3]. Predominantly hydrophobic [PrC4a].
<b>Amounts used</b>
Fraction of EU tonnage used in region: 0.1
Regional tonnage: 1.6 e <sup>7</sup> per year
Fraction of Regional tonnage used locally: 0.0005
Annual site tonnage: 8.2 kilotonnes per year
Maximum daily site tonnage: 23 tonnes per day
<b>Frequency and duration of use</b>
Continuous release [FD2].
Emission days per year: 365
<b>Environmental factors not influenced by risk management</b>
Local freshwater dilution fraction: 10
Local marine dilution fraction: 100
<b>Other Operational Conditions of use affecting environmental exposure</b>
Release fraction to air from process (initial release prior to RMM): 0.0001
Release fraction to wastewater from process (initial release prior to RMM): 0.00001
Release fraction to soil from process (initial release prior to RMM): 0,00001
<b>Conditions and measures related to municipal sewage treatment plant</b>
Estimated substance removal from wastewater via domestic sewage treatment 94.1 %.
Maximum allowable site tonnage (M <sub>Safe</sub> ) based on release following total wastewater treatment removal 350 tonnes per day.
Assumed domestic sewage treatment plant flow 2000 m <sup>3</sup> /day.
<b>Conditions and measures related to external treatment of waste for disposal</b>
ETW1: Combustion emissions limited by required exhaust emission controls.
ETW2: Combustion emissions considered in regional exposure assessment.
<b>Conditions and measures related to external recovery of waste</b>
ERW1: External recovery and recycling of waste should comply with applicable regulations.

**MATERIAL SAFETY DATA SHEET**

**NEOT Diesel -10/-20, NEOT Diesel -10/-20 Premium, NEOT Diesel -25/-35, NEOT Diesel -25/-35 Premium, NEOT Diesel -30/-38, NEOT Diesel -30/-38 Premium**

**Date:** 01.01.2019

**Former date:** 19.03.2018

### **3. Exposure estimation**

#### **3.1 Health**

The ECETOC TRA tool has been used to estimate consumer exposures, consistent with the content of ECETOC Report #107 and the Chapter R15 of the IR&CSA TGD. Where exposure determinants differ to these sources, then they are indicated.

#### **3.2 Environment**

The Hydrocarbon Block Method has been used to calculate environmental exposure with Petrorisk model [EE2] .

### **4. Guidance to check compliance with the exposure scenario**

#### **4.1 Health**

Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented [G22].

Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels [G23].

#### **4.2 Environment**

Further details on scaling and control technologies are provided in SpERC factsheet (<http://cefic.org/en/reach-for-industries-libraries.html>) [DSU4].

**MATERIAL SAFETY DATA SHEET**
**NEOT Diesel -10/-20, NEOT Diesel -10/-20 Premium, NEOT Diesel -25/-35, NEOT Diesel -25/-35 Premium, NEOT Diesel -30/-38, NEOT Diesel -30/-38 Premium**
**Date:** 01.01.2019

**Former date:** 19.03.2018

**AS5: Use of substance in Explosives Manufacture and Use - Professional**
**1. Title**

Use of descriptor	Sector(s) of Use: Professional (SU22)
	Process Categories: PROC1, PROC3, PROC5, PROC8a, PROC8b
	Environmental Release Categories (ERC): 8e  Specific Environmental Release Category: Not Applicable
Processes, Tasks and Activities Covered	Covers exposures arising from the manufacture and use of slurry explosives (including materials transfer, mixing and charging) and equipment cleaning

**2. Operational conditions and risk management measures**
**2.1. Control of worker exposure**

<b>Product characteristics</b>
<b>Physical form of product:</b> Liquid With potential for aerosol generation <b>Vapour pressure (kPa):</b> Liquid, vapour pressure <0.5 kPa at STP [OC3].
<b>Concentration of substance in product</b>
Covers percentage substance in the product up to 100 % (unless stated differently) [G13].
<b>Frequency and duration of use</b>
Covers daily exposures up to 8 hours (unless stated differently) [G2].
<b>Other operational conditions affecting worker exposure</b>
Assumes use at not more than 20 °C above ambient temperature, unless stated differently [G15]. Assumes a good basic standard of occupational hygiene is implemented [G1].
<b>Specific Risk Management Measures and Operational Conditions</b>
<b>General measures applicable to all activities [CS135]</b>
Control any potential exposure using measures such as contained systems, properly designed and maintained facilities and a good standard of general ventilation. Drain down systems and transfer lines prior to breaking containment. Drain down and flush equipment where possible prior to maintenance. Where there is potential for exposure: Ensure relevant staff are informed of exposure potential and aware of basic actions to minimise exposures; ensure suitable personal protective equipment is available; clear up spills and dispose of waste in accordance with regulatory requirements; monitor effectiveness of control measures; provide regular health surveillance as appropriate; identify and implement corrective actions [G25].
<b>General measures (skin irritants) [G19]</b>
Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off skin contamination immediately. Provide basic employee training to prevent / minimise exposures and to report any skin effects that may develop [E3].
<b>General exposures (closed systems) [CS15]</b>

**MATERIAL SAFETY DATA SHEET**
**NEOT Diesel -10/-20, NEOT Diesel -10/-20 Premium, NEOT Diesel -25/-35, NEOT Diesel -25/-35 Premium, NEOT Diesel -30/-38, NEOT Diesel -30/-38 Premium**
**Date:** 01.01.2019

**Former date:** 19.03.2018

Handle substance within a closed system [E47].
<b>General exposures (open systems) [CS16]</b>
Wear suitable gloves tested to EN374 [PPE15].
<b>Process sampling [CS2]</b>
No other specific measures identified [E120].
<b>Bulk transfers [CS14]</b>
Handle substance within a closed system [E47]. Wear suitable gloves tested to EN374 [PPE15].
<b>Drum/batch transfers [CS8]</b>
Use drum pumps or carefully pour from container [E64] Wear chemically resistant gloves (tested to EN374) in combination with basic employee training [PPE16]
<b>Mixing operations (open systems) [CS30]</b>
Provide extract ventilation to points where emissions occur [E54] Wear chemically resistant gloves (tested to EN374) in combination with basic employee training [PPE16]
<b>Production or preparation of articles by tableting, compression, extrusion or pelletisation [CS100]</b>
Wear suitable gloves tested to EN374 [PPE15].
<b>Drum and small package filling [CS8]</b>
Wear suitable gloves tested to EN374 [PPE15]
<b>Laboratory activities [CS36]</b>
No specific measures identified [E118]
<b>Equipment cleaning and maintenance [CS39]</b>
Drain down system prior to equipment break-in or maintenance [E65]. Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training [PPE16].
<b>Storage [CS67]</b>
Handle substance within a closed system [E84].

**2.2. Control of environmental exposure**

<b>Product characteristics</b>
Substance is complex UVCB [PrC3]. Predominantly hydrophobic [PrC4a].
<b>Amounts used</b>
Fraction of EU tonnage used in region: 0.1
Regional tonnage: 1.3 e <sup>4</sup> tonnes per year
Fraction of Regional tonnage used locally: 0.0005
Annual site tonnage: 6.7 tonnes per year
Maximum daily site tonnage: 18 kg per day
<b>Frequency and duration of use</b>
Continuous release [FD2].
Emission days per year: 365
<b>Environmental factors not influenced by risk management</b>
Local freshwater dilution fraction: 10

**MATERIAL SAFETY DATA SHEET**
**NEOT Diesel -10/-20, NEOT Diesel -10/-20 Premium, NEOT Diesel -25/-35, NEOT Diesel -25/-35 Premium, NEOT Diesel -30/-38, NEOT Diesel -30/-38 Premium**
**Date:** 01.01.2019

**Former date:** 19.03.2018

Local marine dilution fraction: 100
<b>Other Operational Conditions of use affecting environmental exposure</b>
Release fraction to air from process (initial release prior to RMM): 0.001 Release fraction to wastewater from process (initial release prior to RMM): 0.02 Release fraction to soil from process (initial release prior to RMM): 0.01
<b>Technical condition and measures at process level (source) to prevent release</b>
TCS 1: Common practices vary across sites thus conservative process release estimates used.
<b>Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil</b>
TCR1b: Risk from environmental exposure is driven by freshwater sediment. TCR9 If discharging to domestic sewage treatment plant, no onsite wastewater treatment required. Treat air emission to provide a typical removal efficiency of N/A %. Treat onsite wastewater (prior to receiving water discharge) to provide the required removal efficiency $\geq 8.8$ %. If discharging to domestic sewage treatment plant, provide the required onsite wastewater removal efficiency of $\geq 0$ %.
<b>Organizational measures to prevent / limit release from site</b>
Do not apply industrial sludge to natural soils [OMS2]. Sludge should be incinerated, contained or reclaimed [OMS3].
<b>Conditions and measures related to municipal sewage treatment plant</b>
Estimated substance removal from wastewater via domestic sewage treatment 94.1 %.
Total efficiency of removal from wastewater after onsite and offsite (domestic treatment plant) RMMs 94.1 %.
Maximum allowable site tonnage ( $M_{Safe}$ ) based on release following total wastewater treatment removal 0.29 tonnes per day.
Assumed domestic sewage treatment plant flow 2000 m <sup>3</sup> /day.
<b>Conditions and measures related to external treatment of waste for disposal</b>
ETW3: External treatment and disposal of waste should comply with applicable regulations.
<b>Conditions and measures related to external recovery of waste</b>
ERW1: External recovery and recycling of waste should comply with applicable regulations.

### 3. Exposure estimation

#### 3.1 Health

The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated [G21].

#### 3.2 Environment

The Hydrocarbon Block Method has been used to calculate environmental exposure with Petrorisk model [EE2] .

**MATERIAL SAFETY DATA SHEET**

**NEOT Diesel -10/-20, NEOT Diesel -10/-20 Premium, NEOT Diesel -25/-35, NEOT Diesel -25/-35 Premium,  
NEOT Diesel -30/-38, NEOT Diesel -30/-38 Premium**

**Date:** 01.01.2019

**Former date:** 19.03.2018

---

## **4. Guidance to check compliance with the exposure scenario**

### **4.1 Health**

Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented [G22].

Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels [G23].

Available hazard data do not enable the derivation of a DNEL for dermal irritant effects [G32]. Available hazard data do not support the need for a DNEL to be established for other health effects [G36]. Risk Management Measures are based on qualitative risk characterisation [G37].

### **4.2 Environment**

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures [DSU1]. Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination [DSU2]. Required removal efficiency for air can be achieved using onsite technologies, either alone or in combination [DSU3]. Further details on scaling and control technologies are provided in SpERC.



**MATERIAL SAFETY DATA SHEET**

**NEOT Diesel -10/-20, NEOT Diesel -10/-20 Premium, NEOT Diesel -25/-35, NEOT Diesel -25/-35 Premium, NEOT Diesel -30/-38, NEOT Diesel -30/-38 Premium**

**Date:** 01.01.2019

**Former date:** 19.03.2018

**AS6: Use in Road and Construction Applications - Professional**

**1. Title**

Use of descriptor	Sector(s) of Use: Industrial (SU22).
	Process Categories: PROC 8a, PROC 8b, PROC 9, PROC 10, PROC 11, PROC 13
	Environmental Release Categories (ERC): 8d, 8f
	Specific Environmental Release Category: ESVOC SpERC 8.15.v1
Processes, Tasks and Activities Covered	Application of surface coatings and binders in road and construction activities, including paving uses, manual mastic and in the application of roofing and water-proofing membranes.

**2. Operational conditions and risk management measures**

**2.1. Control of worker exposure**

<b>Product characteristics</b>
<b>Physical form of product:</b> Liquid <b>Vapour pressure (kPa):</b> Liquid, vapour pressure <0.5 kPa at STP [OC3].
<b>Concentration of substance in product</b>
Covers percentage substance in the product up to 100 % (unless stated differently) [G13].
<b>Frequency and duration of use</b>
Covers daily exposures up to 8 hours (unless stated differently) [G2].
<b>Other operational conditions affecting worker exposure</b>
Assumes use at not more than 20 °C above ambient temperature, unless stated differently [G15]. Assumes a good basic standard of occupational hygiene is implemented [G1].
<b>Specific Risk Management Measures and Operational Conditions</b>
<b>General measures applicable to all activities [CS135]</b>
Control any potential exposure using measures such as contained systems, properly designed and maintained facilities and a good standard of general ventilation. Drain down systems and transfer lines prior to breaking containment. Drain down and flush equipment where possible prior to maintenance. Where there is potential for exposure: Ensure relevant staff are informed of exposure potential and aware of basic actions to minimise exposures; ensure suitable personal protective equipment is available; clear up spills and dispose of waste in accordance with regulatory requirements; monitor effectiveness of control measures; provide regular health surveillance as appropriate; identify and implement corrective actions [G25].
<b>General measures (skin irritants) [G19]</b>
Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off skin

**MATERIAL SAFETY DATA SHEET**
**NEOT Diesel -10/-20, NEOT Diesel -10/-20 Premium, NEOT Diesel -25/-35, NEOT Diesel -25/-35 Premium, NEOT Diesel -30/-38, NEOT Diesel -30/-38 Premium**
**Date:** 01.01.2019

**Former date:** 19.03.2018

contamination immediately. Provide basic employee training to prevent / minimise exposures and to report any skin effects that may develop [E3]. Other skin protection measures such as impervious suits and face shields may be required during high dispersion activities which are likely to lead to substantial aerosol release, e.g. spraying [E4].
<b>Drum/batch transfers (Nondedicated facility) [CS8, CS82]</b>
Wear suitable gloves tested to EN374 [PPE15].
<b>Drum/batch transfers (Dedicated facility) [CS8, CS82]</b>
Wear suitable gloves tested to EN374 [PPE15].
<b>Spraying/fogging by machine application [CS25]</b>
Minimise exposure by partial enclosure of the operation or equipment and provide extract ventilation at openings [E60]. Ensure operation is undertaken outdoors [E69]. Wear gloves tested to EN374 [PPE15].
<b>Manual applications e.g. brushing, rolling [CS13]</b>
Wear chemically resistant gloves (tested to EN374) in combination with specific activity training [PPE17].
<b>Dipping, immersion and pouring [CS4]</b>
Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training [PPE16].
<b>Equipment cleaning and maintenance [CS39]</b>
Drain down system prior to equipment break-in or maintenance [E65]. Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training [PPE16].
<b>Store substance within a closed system [E84]</b>
Handle substance within a closed system [E84].

**2.2. Control of environmental exposure**

<b>Product characteristics</b>
Substance is complex UVCB [PrC3]. Predominantly hydrophobic [PrC4a].
<b>Amounts used</b>
Fraction of EU tonnage used in region: 0.1
Regional tonnage: 31 kilotonnes per year
Fraction of Regional tonnage used locally: 0.0005
Annual site tonnage: 15 tonnes per year
Maximum daily site tonnage: 0.042 tonnes per day
<b>Frequency and duration of use</b>
Continuous release [FD2].
Emission days per year: 365
<b>Environmental factors not influenced by risk management</b>
Local freshwater dilution fraction: 10
Local marine dilution fraction: 100
<b>Other Operational Conditions of use affecting environmental exposure</b>
Release fraction to air from process (initial release prior to RMM): 0.95
Release fraction to wastewater from process (initial release prior to RMM): 0.01
Release fraction to soil from process (initial release prior to RMM): 0.04

**MATERIAL SAFETY DATA SHEET**
**NEOT Diesel -10/-20, NEOT Diesel -10/-20 Premium, NEOT Diesel -25/-35, NEOT Diesel -25/-35 Premium, NEOT Diesel -30/-38, NEOT Diesel -30/-38 Premium**
**Date:** 01.01.2019

**Former date:** 19.03.2018

<b>Technical condition and measures at process level (source) to prevent release</b>
TCS 1: Common practices vary across sites thus conservative process release estimates used.
<b>Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil</b>
TCR1b: Risk from environmental exposure is driven by freshwater sediment. TCR9: If discharging to domestic sewage treatment plant, no onsite wastewater treatment required. Treat air emission to provide a typical removal efficiency of N/A. Treat onsite wastewater (prior to receiving water discharge) to provide the required removal efficiency $\geq 12.2\%$ . If discharging to domestic sewage treatment plant, provide the required onsite wastewater removal efficiency of $\geq 0\%$ .
<b>Organizational measures to prevent / limit release from site</b>
Do not apply industrial sludge to natural soils [OMS2]. Sludge should be incinerated, contained or reclaimed [OMS3].
<b>Conditions and measures related to municipal sewage treatment plant</b>
Estimated substance removal from wastewater via domestic sewage treatment 94.1 %.
Total efficiency of removal from wastewater after onsite and offsite (domestic treatment plant) RMMs 94.1 %.
Maximum allowable site tonnage ( $M_{Safe}$ ) based on release following total wastewater treatment removal 0.62 tonnes per day.
Assumed domestic sewage treatment plant flow 2000 m <sup>3</sup> /day.
<b>Conditions and measures related to external treatment of waste for disposal</b>
ETW3: External treatment and disposal of waste should comply with applicable regulations.
<b>Conditions and measures related to external recovery of waste</b>
ERW1: External recovery and recycling of waste should comply with applicable regulations.

### 3. Exposure estimation

#### 3.1 Health

The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated [G21].

#### 3.2 Environment

The Hydrocarbon Block Method has been used to calculate environmental exposure with Petrorisk model [EE2].

**MATERIAL SAFETY DATA SHEET**

**NEOT Diesel -10/-20, NEOT Diesel -10/-20 Premium, NEOT Diesel -25/-35, NEOT Diesel -25/-35 Premium, NEOT Diesel -30/-38, NEOT Diesel -30/-38 Premium**

**Date:** 01.01.2019

**Former date:** 19.03.2018

## **4. Guidance to check compliance with the exposure scenario**

### **4.1 Health**

Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented [G22]. Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels [G23]. Available hazard data do not enable the derivation of a DNEL for dermal irritant effects [G32]. Available hazard data do not support the need for a DNEL to be established for other health effects [G36]. Risk Management Measures are based on qualitative risk characterisation [G37].

### **4.2 Environment**

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures [DSU1]. Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination [DSU2]. Required removal efficiency for air can be achieved using onsite technologies, either alone or in combination [DSU3]. Further details on scaling and control technologies are provided in SpERC. Factsheet (<http://cefic.org/en/reach-for-industries-libraries.html>) [DSU4].